
Technical information

Productnumber: 13-L120645





Product description

Black plastic transport dolly with a 600x400 base with an open bottom and a coupler. This dolly is designed to help the user move multiple heavy loads in an ergonomically responsible manner. The undercarriage features the innovative "uni-link" feature, which allows interconnection on both the long and short sides. This maximizes the versatility of load movement. Maneuvering several dollies simultaneously in this way requires minimal effort. A practical undercarriage for transporting stacking bins, Euronorm bins or, for example, meat crates. Suitable for industrial bins with euronorm 60x40 cm or 2 pieces 40x30 cm. Equipped with 4 polypropylene swivel casters with diameter 100 mm for smooth running. The dolly is loadable up to 300 kg when evenly distributed. Made of recycled plastic as standard, making it environmentally friendly and cost-effective. Are you temporarily not using the undercarriages? This undercarriage is designed with recesses in the bottom to keep the wheels in place when stacking between them up to 2.3 meters high. This saves considerable space in your workshop or warehouse.

On request also available in other colors or with other wheels, please contact us for the possibilities.

Specifications

Article arrangement: New

Version: connectable, suitable for euro boxes 600x400 mm Wheels front: 2 castor wheels polypropylene, 100 mm

Euronorm (mm): 600 x 400

Ral colour: 9004 Width (mm): 400

Loading capacity (kg): 300 Type number: 13-L1206

Additional specifications: connectable

Type: roll platform Material: polypropylene

Wheels back: 2 castor wheels polypropylene, 100 mm

Colour: black Length (mm): 600 Height (mm): 174 Weight (kg) 2.1

Temperature resistance: -20/+40°C EAN Code (Gtin) 8719424227949

Scan the QR code for more information



























