



Technical information

Productnumber : 77-A121114



Product description

Rolling scaffold MI Tower for rental, demolition or maintenance companies, painters, installers, electricians and freelancers

- Rolling scaffold for 1 person.
- Set up and take down in 10 minutes.
- Very compact to transport.
- Platform with suspension hooks on the side.
- Takes up little floor space.
- Max. load per level (Pressure) (kg/m²): 150 kg/m²
- Working height (m): 6.20 m
- Platform height (m): 4.20 m
- Platform length (m): 1.27 m
- Platform width (m): 0.8 m
- Material: ALUMINUM
- Floor area length (m): 2.93 m
- Floor area width (m): 2.49 m
- Max. load (kg): 150 kg
- Weight (kg): 111 kg
- Wheel Ø (mm): 125 mm
- EN Norm: EN 1004
- Folded width (m): 0.6 m
- Folded length (m): 1.27 m
- Folded height (m): 1.60 m
- Step width (mm): 800 mm

Specifications

Article arrangement: New
Version: quick build

Type: Altrex mobile scaffolding
Material: aluminium



KRUIZINGA.NL®
Opslag- en transportmiddelen

KRUIZINGA.DE®
Lager- und Transportmittel

KRUIZINGA.FR®
Stockage et ressources de transport

KRUIZINGA.COM®
Material handling equipment

Image not found or type unknown

Subgroup: Mobile scaffolding

Width (mm): 1200

Depth (mm): 700

Weight (kg): 111

Type number: C003002

Horizontal platform (mm): 4200

EAN Code (Gtin) 8719424208184

Technical information

Productnumber : 77-A121114

Colour: alu silver

Height (mm): 5000

Loading capacity (kg): 150

Options: Norm: EN1004

Additional specifications: type use: professional

Work height (mm): 6200

Scan the QR code for more information



KRUIZINGA.NL[®]
Opslag- en transportmiddelen

KRUIZINGA.DE[®]
Lager- und Transportmittel

KRUIZINGA.FR[®]
Stockage et ressources de transport

KRUIZINGA.COM[®]
Material handling equipment