
Technical information

Productnumber: 75.146.686.104





Product description

Transport swivel castor with brake made of pressed sheet steel, plate fitting, grey non-marking thermoplastic rubber tyre, Wheel-Ø 100, 120KG

Wheel: grey non-marking TPR rubber tyre, with polypropylene wheel core, central ball bearing,

Advantages: The solid rubber tyres have a hardness of 85° Shore A and offer good driving characteristics, roll silently, are impact and shock resistant, corrosion resistant and have medium rolling resistance.

Applications: Versatile use for light transport in e.g. offices, warehouses, shops and institutions. Low-noise, impact-resistant and vibration-damping. Swivel castor for light applications. Less suitable for continuous static use under maximum load.

Suitable surface: Flat or slightly uneven. Non-striping tyre for use on ceramic tiles, linoleum, etc. Suitable environment: Dry and not permanently damp. With light acids and bases.

Specifications

Article arrangement: New Version: Ø 100 mm

Top: base plate 105x85 mm

Bolt hole: Ø 9 mm

Surface treatment: galvanized

Width (mm): 36

Loading capacity (kg): 120 Type number: 146686104

Temperature resistance: -20 / +60

Scan the QR code for more information

Type: castor wheel with brake Material: thermo rubber Hole centres: 80x60 mm Colour: colorless

Length (mm): 100 Height (mm): 128

Wheel bearing: ball bearing Wheels diameter: 100











Technical information

Productnumber: 75.146.686.104

