



Technical information

Productnumber : 75.140.116.203



Product description

Benefits: Versatile use with excellent rolling characteristics. Low noise and vibration damping.

Applications: Industrial carts, material handling in factories, waste containers, transport containers, metal working and chemical companies, medium load roll containers, tool trolleys, warehouse carts.

Suitable surface: Almost every surface: uneven surfaces such as pavers, damaged floors and obstacles such as thresholds.

Suitable environment: Dry and not permanently humid. For mild chemicals.

Specifications

Article arrangement: New

Version: Ø 200 mm

Top: bolt hole fitting 13 mm

Colour: colorless

Length (mm): 200

Height (mm): 235

Wheel bearing: ball bearing

Temperature resistance: -20 / +60°C

Type: castor wheel with brake

Material: elastic rubber band

Bolt hole: Ø 13 mm

Surface treatment: galvanized

Width (mm): 50

Loading capacity (kg): 400

Type number: 75116100

EAN Code (Gtin) 8719424147681

Scan the QR code for more information



KRUIZINGA.NL®
Opslag- en transportmiddelen

KRUIZINGA.DE®
Lager- und Transportmittel

KRUIZINGA.FR®
Stockage et ressources de transport

KRUIZINGA.COM®
Material handling equipment