

Image not found or type unknown



## Technical information

**Productnumber : 75.140.652.120**



### Product description

Benefits: The solid rubber tires have a hardness of 80° Shore A ° Shore A and offer good handling, quiet rolling, they are shock and impact resistant, corrosion resistant and they have an average rolling resistance.

Applications: Versatile use for light transport in e.g. offices, warehouses, shops and institutions. Low noise, shock and vibration damping. Castor for lightweight applications. Less suitable for prolonged use under maximum static load.

Suitable surface: Almost every surface: uneven surfaces such as pavers, damaged floors and obstacles such as thresholds. The tire may leave black traces on the floor.

Suitable environment: Dry and not permanently humid. For mild acids and alkalis.

### Specifications

Article arrangement: New

Version: Ø 125 mm

Top: bolt hole fitting 13 mm

Colour: colorless

Length (mm): 125

Height (mm): 155

Wheel bearing: roller bearing

Temperature resistance: -20 / +60°C

Type: castor wheel

Material: solid rubber tyre

Bolt hole: ø 13 mm

Surface treatment: galvanized

Width (mm): 37

Loading capacity (kg): 130

Type number: 75652800

EAN Code (Gtin) 8719424147537

Scan the QR code for more information



**KRUIZINGA.NL®**  
Opslag- en transportmiddelen

**KRUIZINGA.DE®**  
Lager- und Transportmittel

**KRUIZINGA.FR®**  
Stockage et ressources de transport

**KRUIZINGA.COM®**  
Material handling equipment