

Image not found or type unknown



Technical information

Productnumber : 75.140.992.200



Product description

Benefits: The solid rubber tires have a hardness of 90° Shore A ° Shore A and offer good handling, quiet rolling, they are shock and impact resistant, corrosion resistant and they have an average rolling resistance.

Applications: Industrial carts, material handling in factories, waste containers, transport containers, metal working and chemical companies, medium load roll containers, tool trolleys, warehouse carts.

Suitable surface: Almost every surface: uneven surfaces such as pavers, damaged floors and obstacles such as thresholds. The tire may leave black traces on the floor.

Suitable environment: Dry and not permanently humid. For mild acids and alkalis.

Specifications

Article arrangement: New

Version: Ø 200 mm

Top: bolt hole fitting 13 mm

Colour: colorless

Length (mm): 200

Height (mm): 235

Wheel bearing: roller bearing

Temperature resistance: -20 / +60°C

Type: castor wheel

Material: standard rubber band

Bolt hole: Ø 13 mm

Surface treatment: galvanized

Width (mm): 50

Loading capacity (kg): 200

Type number: 75992800

EAN Code (Gtin) 8719424147438

Scan the QR code for more information



KRUIZINGA.NL®
Opslag- en transportmiddelen

KRUIZINGA.DE®
Lager- und Transportmittel

KRUIZINGA.FR®
Stockage et ressources de transport

KRUIZINGA.COM®
Material handling equipment